# st ecobee 3



## Compatibility

- Conventional (2H/2C)
- Heat pump (4H/2C) incl. 2-stage auxiliary heat
- · Gas, oil, electric
- Dual fuel
- Humidifier, dehumidifier, ventilator, HRV or ERV

### Wire terminals

• Rc

Rн

• G

- Y1

O/B

• ACC +

• ACC -

- Y2
- W1 (AUX1)
- C
   W2 (AUX2)

# **Powering method**

Wired 24VAC through terminals C and either Rh or Rc.

Power Extender Kit (included) enables you to reliably power your thermostat without having to run a fifth wire.

# Power consumption

Less than 3.5VA

# Connectivity and security

- 2 radios 915MHZ, wi-fi
- 802.11 b/g/n @ 2.4 GHZ
- WEP 64, WEP 128, WPA and WPA2 encryption methods
- DHCP (dynamic) or static IP addressing
- 168 bit SSL encryption

#### **Bandwidth**

15-20 MB/month

### **Sensors**

#### Thermostat

- Temperature
- Motion
- Proximity
- Humidity

### Green

- · Recyclable packaging
- · Mercury free
- · Arsenic free
- PVC free
- ROHS compliant

## Temperature range

Desired Temperature: 45° to 92°F

(7° to 33°C)

Display: 40° to 100°F (5° to 37°C) Sensitivity: +/- 1°F (+/- 0.5°C) Operating: 32° to 130°F (0° to 55°C)

# **Humidity range**

Display: 20% to 90% RH Sensitivity: +/- 5% RH

Operating: 5% to 95% RH (non condensing)

# Storage

- -31° to 113°F (-35° to 45°C)
- 5% to 95% RH (non condensing)

### HomeKit-enabled

HomeKit requires an iPhone, iPad, or iPod touch with iOS 8.1 or later.

Controlling HomeKit-enabled accessories away from home requires an Apple TV (3rd generation or later) with Apple TV software 7.0 or later and an iPhone, iPad, or iPod touch with iOS 8.1 or later.



### What's in the box

- ecobee3 thermostat
- · Remote Sensor with detachable stand
- · Power Extender Kit
- 2 trim plates (small and large)
- · Quick Start Guide
- Installation Guide with wire labels
- · Mounting screws and drywall plugs
- · Double-sided adhesives

# **Product dimensions**

#### ecobee3

Remote sensor

Temperature

Motion

Height: 3.93 in / 100 mm Width: 3.93 in / 100 mm Depth: 0.9 in / 22 mm

#### Remote Sensor

Height: 1.7 in / 44 mm (with stand) 2.2 in / 54 mm Width: 1.7 in / 44 mm Depth: 0.8 in / 20 mm

#### Power Extender Kit

 Height:
 2.0 in / 50 mm

 Width:
 2.7 in / 68 mm

 Depth:
 0.8 in / 20 mm

### Small trim plate

 Height:
 3.93 in / 100 mm

 Width:
 3.93 in / 100 mm

 Depth:
 0.5 in / 12 mm

#### Large trim plate

Height: 5.9 in / 150 mm Width: 5.9 in / 150 mm Depth: 0.6 in / 15 mm

#### Warranty

3-year warranty

Languages

English

#### Display

3.5" full-color LCD touch screen320 x 480 pixel display